

# JetAire™ High Velocity Fan



MEETS  
**OSHA**  
REQUIREMENTS

*Shown  
with Optional  
Oscillator and  
Pedestal*

*(see back side for  
other options)*

*Triangle's JetAire High Velocity Fans are manufactured with durable polypropylene barrels and equipped with totally enclosed motors.*

- ◆ Available with 24" and 30" dia. fan blades
- ◆ Ideal for industrial/commercial and Golf Course applications
- ◆ Available with or without oscillation
- ◆ Moves a large concentration of air at distances of 100 feet or more
- ◆ Tilttable head for desired direction of air flow
- ◆ Optional mounting equipment for adapting fans to various applications such as pole, tree, column, or beam mount
- ◆ Motors are available in single or three phase
- ◆ Can be equipped with cool mist system
- ◆ Choice of Industrial Gray or Hunter Green



*HVD Dolly  
Mount is  
designed for  
easy mobility*

Patent  
#5,480,282



**TRIANGLE ENGINEERING  
OF ARKANSAS, INC.**

E-mail: [mail@trianglefans.com](mailto:mail@trianglefans.com) • Website: [www.trianglefans.com](http://www.trianglefans.com)  
1101 North Redmond Road • Jacksonville, Arkansas 72076  
(501) 982-7558 • **1-800-255-9014** • Fax (501) 982-5691



# JetAire™ High Velocity Fan

## OPTIONS



**HV Basic JetAire Fan**  
(Mounting sold separately)



**HV JetAire**  
Chain suspended



**HVD JetAire**  
Dolly mount




**45" Pedestal Mount & Base**



**Vertical Beam Mounting Bracket**



**Horizontal Mounting Bracket for Post or Tree**



**The JetAire may be mounted on a permanent, owner-provided post**  
(3" schedule 40 pipe)

115/230/60/1 Totally Enclosed Motor		230/460/60/3 Totally Enclosed Motor		HP	Blade Dia.	CFM	RPM	Air Velocity, FPM at a Distance of:				Ship Wt.
Model No.	Amps	Model No.	Amps					50'	75'	100'	125'	
HV 2413	8.0/4.0	HV 2413-46	2.6/1.3	1/2	24"	5,600	1,075	475	330	247	192	173
HV 2413-OC		HV 2413-46-OC										183
HV 2415	10.6/5.3	HV 2415-46	3.6/1.8	1	24"	5,900	1,140	495	340	260	200	178
HV 2415-OC		HV 2415-46-OC										188
HV 3013	8.0/4.0	HV 3013-46	2.6/1.3	1/2	30"	7,900	1,075	595	395	297	225	173
HV 3013-OC		HV 3013-46-OC										183
HVD 3013		HVD 3013-46										221
HV 3015	10.6/5.3	HV 3015-46	3.6/1.8	1	30"	10,600	1,140	665	435	320	250	178
HV 3015-OC		HV 3015-46-OC										188
HVD 3015		HVD 3015-46										218

HMB 2430 = Post Mounting Bracket for HV 24 or HV 30  
 HTB 2430 = Tree Mounting Bracket for HV 24 or HV 30  
 VMB 2430 = Beam Mounting Bracket for HV 24 or HV 30  
 PB 2430 = Pedestal Base for HV 24 or HV 30

OC = Oscillator; available for all fans except the HVD series.  
 HVD = Dolly mounted, tiltable head  
 Note: Standard barrel color Industrial Gray; also available in Hunter Green

Specifications subject to change without notice. Printed in USA. Revised 3/08

For more information, contact a Triangle Dealer or Distributor near you...