

Master Breeze™

PEDESTAL FANS

24" and 30" Industrial Grade Fans and Accessories



*Typical AMB
Pedestal Fan
and Base
shown
(see back side for
mounting options)*



Triangle's pedestal fans have a superior design and proven performance that provide powerful, convenient air circulation wherever its needed.

Master Breeze Features...

- 115V, 60Hz, 1 phase motors with thermal overload protection
- OSHA compliant chrome plated fan guards
- Easy to assemble
- Heavy duty 12' power cord with molded grounded plug
- 30" diam. steel base for maximum stability
- Optional mounting accessories and wheel kits are available
- Balanced 3-paddle aluminum blade assembly
- Oscillating feature available
- Telescoping adjustable pole provides heights from 4'4" to 7'4"
- 2 and 3 speeds available, providing air movement from 5,600 to 9,600 cfm



TRIANGLE ENGINEERING OF ARKANSAS, INC.

E-mail: mail@trianglefans.com • Website: www.trianglefans.com

1101 North Redmond Rd. • Jacksonville, AR 72076


(501) 982-7558 • Fax (501) 982-5691

1-800-255-9014




PEDESTAL FANS

With Wall/Column Mounting Bracket, Suspension Bracket or Hanger Bracket and Optional Wheel Kit



WC

Triangle's adjustable fan head assembly can be used with the **Wall/Column Mounting Bracket**. This bracket allows the fan to be easily and securely mounted to a beam, column or any other flat surface. The extended head assembly permits the fan to be tilted or turned to direct the air flow in the desired



S

direction. The wall/column bracket has a powder coat finish. Mounting bolts are not included.


The **Suspension Bracket** allows fan head to be suspended from any 2"x beam or joist. Bracket has a galvanized finish, mounting bolts not included. This bracket **CAN NOT** be used with an oscillating head.



HB

The **Hanger Bracket** is for use with an oscillating head. Bracket has a durable, powder coat finish. Mounting bolts not included.

The optional **Wheel Kit** is simple to install and makes any pedestal fan easily portable.



WK

Model No.	Blade Diameter	CFM Hi/Lo	Motor HP	Amps	Shipping Weight
AMB 2421 H	24"	6,100/4,300	1/4	2.6	42
AMB 2431 H OC	24"	6,000/4,000/3,000	1/4	2.7	47
AMB 2423 H	24"	7,800/5,300	1/2	6.2	42
AMB 3021 H	30"	7,200/5,400	1/4	2.6	49
AMB 3031 H OC	30"	7,100/5,100/3,100	1/4	2.7	54
AMB 3023 H	30"	8,800/6,400	1/2	6.2	49
AMB 2421 WC	24"	6,100/4,300	1/4	2.6	48
AMB 2431 WC OC	24"	6,000/4,000/3,000	1/4	2.7	53
AMB 2423 WC	24"	7,800/5,300	1/2	6.2	49
AMB 3021 WC	30"	7,200/5,400	1/4	2.6	48
AMB 3031 WC OC	30"	7,100/5,100/3,100	1/4	2.7	53
AMB 3023 WC	30"	8,800/6,400	1/2	6.2	49
AMB 2421 S	24"	6,100/4,300	1/4	2.6	50
AMB 2423 S	24"	7,800/5,300	1/2	6.2	50
AMB 3021 S	30"	7,200/5,400	1/4	2.6	54
AMB 3023 S	30"	8,800/6,400	1/2	6.2	54
AMB 2431 HB OC	24"	6,000/4,000/3,000	1/4	2.7	58
AMB 3031 HB OC	30"	7,100/5,100/3,100	1/4	2.7	59
AMB 2421	24"	6,100/4,300	1/4	2.6	80
AMB 2431 OC	24"	6,000/4,000/3,000	1/4	2.7	85
AMB 2423	24"	7,800/5,300	1/2	6.2	80
AMB 3021	30"	7,200/5,400	1/4	2.6	83
AMB 3031 OC	30"	7,100/5,100/3,100	1/4	2.7	88
AMB 3023	30"	8,800/6,400	1/2	6.2	83
WK 2430 Wheel Kit					15

H = Head only
 WC = Wall/Column mounting bracket supplied in place of pedestal and base
 S = Suspension bracket supplied in place of pedestal and base
 HB = Hanger Bracket for Oscillating fan only
 OC = Three-speed oscillator motor. Standard RPM on high speed is 1100

All fan motors are 115 Volts • AMB carton size: 36½" x 14½" x 43½"