

"V SERIES" BELT DRIVEN WALL PANEL EXHAUST FAN



V & RV Series fans are designed with an Automatic Belt Tensioner providing low maintenance and extending the life of the belt and motor

- * High quality heavy duty components are coated with a durable powder coat finish
 - * Single Phase Open Motors
 - * All dual voltage motors are tested and factory wired at 115 volt
 - * Two speed single phase motors available up to 1/2 hp 115V
- Consult factory for price and delivery

| SPECIFICATIONS "V" SERIES | | | | | | | | | | | |
|---------------------------|--------------|---------|-----|-------|--------|--------|----------|---------|---------------|----------------|---------|
| BLADE DIA | MODEL NUMBER | VOLTS | HP | SPEED | AMPS | CFM | | | APPROX WEIGHT | OUTSIDE SQ DIM | DEPTH |
| | | | | | | 0.0 SP | 0.125 SP | 0.25 SP | | | |
| 24" | V 2412 V | 115 | 1/3 | 1 | 6.5 | 3,920 | 2,070 | 930 | 53 | 30" | |
| 30" | V 3012 V | 115 | 1/3 | 1 | 6.5 | 6,420 | 4,980 | 1,790 | 55 | 34" | |
| | V 3013 V | 115 | 1/2 | 1 | 11 | 9,560 | 7,770 | 4,850 | 63 | | |
| 36" | V 3613 V | 115 | 1/2 | 1 | 11 | 10,900 | 9,160 | 4,310 | 67 | 40" | 16 1/4" |
| 42" | V 4213 V | 115 | 1/2 | 1 | 11 | 14,200 | 11,600 | 5,470 | 87 | 46" | |
| 48" | V 4813 V | 115 | 1/2 | 1 | 11 | 17,100 | 11,500 | 3,900 | 104 | 52" | |
| | V 4814 U | 115/230 | 3/4 | 1 | 13/6.5 | 18,100 | 13,800 | 6,370 | 109 | | |

"RV SERIES" BELT DRIVEN WALL PANEL SUPPLY FAN



| SPECIFICATIONS "RV" SERIES | | | | | | | | | | | |
|----------------------------|--------------|---------|-----|-------|--------|--------|----------|---------|---------------|----------------|---------|
| BLADE DIA | MODEL NUMBER | VOLTS | HP | SPEED | AMPS | CFM | | | APPROX WEIGHT | OUTSIDE SQ DIM | DEPTH |
| | | | | | | 0.0 SP | 0.125 SP | 0.25 SP | | | |
| 24" | RV 2412 V | 115 | 1/3 | 1 | 6.5 | 3,920 | 2,070 | 930 | 53 | 30" | |
| 30" | RV 3012 V | 115 | 1/3 | 1 | 6.5 | 6,420 | 4,980 | 1,790 | 55 | 34" | |
| | RV 3013 V | 115 | 1/2 | 1 | 11 | 9,560 | 7,770 | 4,850 | 63 | | |
| 36" | RV 3613 V | 115 | 1/2 | 1 | 11 | 10,900 | 9,160 | 4,310 | 67 | 40" | 16 1/4" |
| 42" | RV 4213 V | 115 | 1/2 | 1 | 11 | 14,200 | 11,600 | 5,470 | 87 | 46" | |
| 48" | RV 4813 V | 115 | 1/2 | 1 | 11 | 17,100 | 11,500 | 3,900 | 104 | 52" | |
| | RV 4814 U | 115/230 | 3/4 | 1 | 13/6.5 | 18,100 | 13,800 | 6,370 | 109 | | |

Performance shown is for installation type A: free inlet, free outlet. Performance ratings do not include the effects of accessories.