

## " VID SERIES" DIRECT DRIVE INDUSTRIAL WALL FAN



- \* Venturi coated with a durable polyester powder coat finish
- \* Rugged heavy gauge galvanized housing
- \* Totally Enclosed Motors
- \* Single Phase fans include cord and molded plug

### Accessories:

- Screen Guard (Meets OSHA requirements)
- IWS Automatic Exhaust Wall Shutter
- RIWS Supply Wall Shutter (Operator required)
- Shutter Motor or Pull Chain Operator
- Rain Hood

SPECIFICATIONS "VID" SERIES												
BLADE DIA	MODEL NUMBER	VOLTS	PH	HP	AMPS	CFM				APPROX WEIGHT	OUTSIDE SQ DIMENSION	DEPTH
						0.0 SP	0.125 SP	0.25 SP	0.5 SP			
24"	VID 2413 TV	115	1	1/2	6	5,910	5,080	3,740		99	30 3/4"	20"
	VID 2413 TW	230	1	1/2	3	5,910	5,080	3,740		99		
30"	VID 3013 TV	115	1	1/2	6	8,770	7,600	6,240		105	34 3/4"	20"
	VID 3013 TW	230	1	1/2	3	8,770	7,600	6,240		105		
36"	VID 3613 TV	115	1	1/2	6	10,800	8,840	6,550		115	40 3/4"	20"
	VID 3613 TW	230	1	1/2	3	10,800	8,840	6,550		115		
	VID 3615 TV	115	1	1	9.1	13,500	11,630	9,100	3,930	140		
	VID 3615 TW	230	1	1	4.6	13,500	11,630	9,100	3,930	140		
	VID 3615 TX	230/460	3	1	5.2/2.6	13,100	11,400	9,200	3,440	140		
	VID 4213 TV	115	1	1/2	6	13,190	9,900	4,840		145		
42"	VID 4213 TW	230	1	1/2	3	13,190	9,900	4,840		145	46 3/4"	20"
	VID 4215 TV	115	1	1	9.1	16,300	14,200	11,500	4,000	170		
	VID 4215 TW	230	1	1	4.6	16,300	14,200	11,500	4,000	170		
	VID 4215 TX	230/460	3	1	5.2/2.6	16,100	13,800	11,400	4,370	165		
48"	VID 4815 TV	115	1	1	9.1	19,900	15,800	10,500		180	52 3/4"	20"
	VID 4815 TW	230	1	1	4.6	19,900	15,800	10,500		180		
	VID 4815 TX	230/460	3	1	5.2/2.6	19,900	16,000	11,800		175		

Performance shown is for installation type A: free inlet, free outlet. Performance ratings do not include the effects of accessories.

Note: All units are made to order and are not returnable