



"VIK SERIES" BELT DRIVEN INDUSTRIAL WALL EXHAUST FAN PACKAGE

The VIK Series fan is a combination of the VI Series fan, a heavy duty intake screen guard and an automatic exhaust shutter for convenient installation.



- * Rolled Inlet Venturi for efficient air flow
- * Venturi coated with a durable polyester powder coat finish
- * Rugged heavy gauge galvanized steel housing
- * Aluminum shutter blades
- * Heavy duty black polyester powder coated screen guard.
- * Single Phase motors are factory prewired 115 volts with a power cord and a molded plug.

1.5 hp and smaller are designed with Triangle's Exclusive "X-Wing" Belt Tensioner providing low maintenance by extending the life of the belt and motor
2 hp and larger have a standard stationary motor mount



X-WING BELT TENSIONER

Optional Features:

- * When ordering Totally enclosed motors, add T suffix to model number. Consult factory for price and delivery
- * When ordering Hazardous Location fans, add HL suffix to model number
Hazardous Location (Explosion proof motor with aluminum blades)
Motors are Division 1, Class 1 Group D and Class II Group F&G
Consult factory for price and delivery
- * Two speed single phase motors available up to 1/2 hp 115V only
Consult factory for price and delivery

| SPECIFICATIONS "VIK" SERIES | | | | | | | | | | | | |
|-----------------------------|--------------|---------|-------|---------|-----------|--------|----------|---------|--------|---------------|----------------|-------|
| BLADE DIA | MODEL NUMBER | VOLTS | PH | HP | AMPS | CFM | | | | APPROX WEIGHT | OUTSIDE SQ DIM | DEPTH |
| | | | | | | 0.0 SP | 0.125 SP | 0.25 SP | 0.5 SP | | | |
| 24" | VIK 2412 V | 115 | 1 | 1/3 | 6.5 | 4,190 | 3,250 | 1,950 | | 150 | 30 3/4" | |
| | VIK 2412 X | 230/460 | 3 | 1/3 | .8/1.6 | 4,190 | 3,250 | 1,950 | | 150 | | |
| | VIK 2413 V | 115 | 1 | 1/2 | 11 | 4,510 | 3,550 | 2,120 | | 155 | | |
| | VIK 2413 W | 230 | 1 | 1/2 | 5.5 | 4,510 | 3,550 | 2,120 | | 155 | | |
| | VIK 2413 X | 230/460 | 3 | 1/2 | 2.0/1.0 | 4,510 | 3,550 | 2,120 | | 155 | | |
| 30" | VIK 3012 V | 115 | 1 | 1/3 | 6.5 | 7,080 | 6,050 | 4,940 | | 181 | 34 3/4" | 24" |
| | VIK 3013 V | 115 | 1 | 1/2 | 11 | 9,180 | 7,880 | 6,430 | 1,400 | 181 | | |
| | VIK 3013 W | 230 | 1 | 1/2 | 5.5 | 9,180 | 7,880 | 6,430 | 1,400 | 181 | | |
| | VIK 3013 X | 230/460 | 3 | 1/2 | 2.0/1.0 | 9,180 | 7,880 | 6,430 | 1,400 | 181 | | |
| | VIK 3014 U | 115/230 | 1 | 3/4 | 13/6.5 | 10,200 | 8,900 | 6,340 | | 185 | | |
| 36" | VIK 3014 X | 230/460 | 3 | 3/4 | 2.8/1.4 | 10,200 | 8,900 | 6,340 | | 185 | 40 3/4" | |
| | VIK 3613 V | 115 | 1 | 1/2 | 11 | 10,800 | 8,840 | 6,550 | | 200 | | |
| | VIK 3613 X | 230/460 | 3 | 1/2 | 2.0/1.0 | 10,800 | 8,840 | 6,500 | | 200 | | |
| | VIK 3614 U | 115/230 | 1 | 3/4 | 13/6.5 | 11,100 | 7,850 | 4,380 | | 214 | | |
| | VIK 3614 X | 230/460 | 3 | 3/4 | 2.8/1.4 | 11,100 | 7,850 | 4,380 | | 218 | | |
| 42" | VIK 3615 U | 115/230 | 1 | 1 | 11/5.5 | 12,100 | 9,030 | 5,970 | | 225 | 46 3/4" | 24" |
| | VIK 3615 X | 230/460 | 3 | 1 | 4.0/2.0 | 12,100 | 9,030 | 5,970 | | 225 | | |
| | VIK 3616 U | 115/230 | 1 | 1 1/2 | 15/4.5 | 13,110 | 9,820 | 6,450 | | 247 | | |
| | VIK 3616 X | 230/460 | 3 | 1 1/2 | 4.8/2.4 | 13,100 | 9,820 | 6,450 | | 247 | | |
| | VIK 3617 U | 115/230 | 1 | 2 | 20.4/10.2 | 12,780 | 11,790 | 10,800 | 8,250 | 282 | | |
| 42" | VIK 3617 X | 230/460 | 3 | 2 | 6.4/3.2 | 12,780 | 11,790 | 10,800 | 8,250 | 262 | 46 3/4" | 24" |
| | VIK 3618 X | 230/460 | 3 | 3 | 8.0/4.0 | 15,400 | 14,200 | 13,000 | 9,970 | 337 | | |
| | VIK 4213 V | 115 | 1 | 1/2 | 11 | 13,000 | 9,730 | 4,270 | | 239 | | |
| | VIK 4213 X | 230/460 | 3 | 1/2 | 2.0/1.0 | 13,000 | 9,730 | 4,270 | | 239 | | |
| | VIK 4214 U | 115/230 | 1 | 3/4 | 13/6.5 | 14,600 | 12,000 | 6,780 | | 242 | | |
| 42" | VIK 4214 X | 230/460 | 3 | 3/4 | 2.8/1.4 | 14,600 | 12,000 | 6,780 | | 242 | 46 3/4" | 24" |
| | VIK 4215 U | 115/230 | 1 | 1 | 11/5.5 | 16,000 | 11,600 | 6,040 | | 252 | | |
| | VIK 4215 X | 230/460 | 3 | 1 | 4.0/2.0 | 16,000 | 11,600 | 6,040 | | 252 | | |
| | VIK 4216 U | 115/230 | 1 | 1 1/2 | 15/7.5 | 17,200 | 14,700 | 10,800 | | 273 | | |
| VIK 4216 X | 230/460 | 3 | 1 1/2 | 4.8/2.4 | 17,200 | 14,700 | 10,800 | | 263 | | | |

Performance shown is for installation type A: free inlet, free outlet.

Performance ratings do not include the effects of accessories.

Note: All units are made to order and are not returnable