

THE PORTABLE COOLER™

The highest quality, most complete line of heavy duty fans available. Our line of portable direct drive fans are rugged, low-cost air movers. They are used to spot cool assembly lines, machine shops, bakeries, loading docks, laundries, gymnasiums, auto repair facilities, warehouses or anywhere a high volume of air movement is required.

Features

- Direct drive
- Heavy gauge steel barrels
- Deep pitched blades for maximum airflow
- OSHA approved spiral wound guard
- 115 volt, 60 hertz, single phase, oneor two-speed motors









PORTABLE COOLER HD

- Tough, rugged and durable
- Deep pitched blades
- Switch Guard

The Portable Cooler HD is one of the most rugged and dependably built, direct drive fans on the market and is engineered to provide long lasting spot cooling for people, products and equipment.

Model	Blade Diameter	СҒМ	RPM	НР	Amps	Width	Depth	Height	Approximate Weight
PC3613	36"	10,900	825	1/2	6.0	39"	21"	40"	111
PC3623	36"	10,900 / 8,800	825 / 680	1/2	6.0	39"	21"	40"	111
PC4213	42"	13,600	825	1/2	6.0	45"	21"	46"	121
PC4223	42"	13,600 / 10,500	825 / 680	1/2	6.0	45"	21"	46"	121
PC4815	48"	19,100	850	1	9.1	51"	25"	52"	193



THE PORTABLE COOLER

- Economical cooling
- Durable steel barrel
- Two-speed

The Portable Cooler is our most economical direct drive portable barrel fan. It offers superb airflow in a rugged and easy to move design.

Model	Blade Diameter	CFM	RPM	НР	Amps	Width	Depth	Height	Approximate Weight
QBD3623	36"	10,900 / 8,800	800/725	1/2	6.1	39"	21"	40"	96
QBD4223	42"	13,200 / 10,200	800/725	1/2	6.1	45"	21"	45"	101



THE HBPC

- Tough, rugged and durable
- Full width easy grip handle
- Tilts up or down with positive tilt lock knob

The "HBPC" employs the same great design of the Portable Cooler HD while adding a cradle mount, allowing for precise, directional cooling of people, products or equipment.

Model	Blade Diameter	CFM	RPM	НР	Amps	Width	Depth	Height	Approximate Weight
HBPC3613	36"	10,900	825	1/2	6.0	45"	27"	50"	192
HBPC3623	36"	10,900 / 8,800	825 / 680	1/2	6.0	45"	27"	50"	192
HBPC4213	42"	13,600	825	1/2	6.0	51"	27"	54"	202
HBPC4213-W*	42"	13,600	825	1/2	3.0	51"	27"	54"	202
HBPC4223	42"	13,600 / 10,500	825 / 680	1/2	6.0	51"	27"	54"	202
HBPC4815	48"	19,100	850	1	9.1	58"	27"	60"	228
HBPC4815-W*	48"	19,100	850	1	4.5	58"	27"	60"	228

^{*230}V 1 Ø motor



PORTABLE COOLER MINI

- Deep pitched blades
- Spiral wound wire guard
- 115 volt 60hz two-speed motor
- Caddy cart handle for easy maneuverability

The Portable Cooler Mini has all of the great design of the Portable Cooler HD but in a slim, light weight design, making it ideal for workshops, garages and sporting events.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
PC3021	30"	8,200 / 6,600	1,090 / 1,010	1/4	3.5	33"	15"	34"	55



CONTRACTOR'S FAN

- Tilt up or down 90° degrees
- 115 volt, 60hz, two-speed motor
- Spiral wound wire guard

Triangle's Contractor Fan is great for home use, farm use, workshops, garages, sporting events, and campsites.

Model	Blade Diameter	СҒМ	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
CF2421	24"	3,800 / 3,200	1,100 / 950	1/4	3.5	29"	16"	31"	48